

Tel: 215.591.3610

Fax: 215.591.3620

## Ethylene Bis-Stearamide (EBS) Tallow Beaded

## PRODUCT DATA SHEET

PARAMETERS	SPECIFICATION	TEST METHODS
Appearance	Beaded	Visual
Acid Value	8 max	Vendor
Color, Gardner	5 max	Vendor
Melting Point, °C	140 – 145	Vendor
Neutralization Value	2 max	Vendor
Mesh, %:		
Thru 10 Mesh	10 max	Vendor
Thru 100 Mesh	90 min	Vendor
Typical Properties:		
Flash Point, °C	285	Vendor
Mean Particle Size (microns)	570	Vendor

## **Inquiries:**

Acme-Hardesty Co. 450 Sentry Parkway Blue Bell, PA 19422 (800) 223-7054 csc@acme-hardesty.com

The data herein are based on our current knowledge and believed to be reliable. They are intended for use by persons having technical skill and at their own discretion and risk. Due to numerous factors that may affect handling, processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any data given herein may change without prior notice and do not constitute a contractual agreement regarding quality.

Acme-Hardesty Co., specifically disclaims any implied warranties of merchantability, suitability or fitness for a particular purpose or application, and assumes no liability in connection with the use of this information. Final determination of suitability is the sole responsibility of the user who alone knows the conditions of intended use.

Date: February 12, 2014

/1165

