



ACME-HARDESTY
A division of
JACOB STERN & SONS, INC.
- SINCE 1857 -

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 05/12/2017 Date of Issue: 05/12/2017

Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product Identifier

Product Form: Substance

Product Name: Lauryl Alcohol Ethoxylate (3 Mole)

CAS-No.: 68551-12-2

Synonyms: Laureth-3 (INCI Name); Ethoxylated lauryl alcohol 3 EO; Alcohols, C12-16, ethoxylated; Ethoxylated lauryl myristyl alcohol 3; EO; Ethoxylated dodecyl tetradecyl alcohol 3 EO; Polyethylene glycol dodecyl tetradecyl ether; Poly(oxy 1,2 ethanediyl),.alpha.-dodecyl-tetradecyl.omega.-hydroxy-; Polyoxyethylene lauryl myristyl ether;

1.2. Intended Use of the Product

Use of the substance/mixture: Industrial Use

1.3. Name, Address, and Telephone of the Responsible Party

Company

Acme-Hardesty Co
450 Sentry Parkway
Blue Bell, PA 19422
T 866-226-3834 T 215-591-3610

www.acme-hardesty.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Skin Irrit. 2 H315

Eye Dam. 1 H318

Aquatic Acute 1 H400


Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 - Causes skin irritation

H318 - Causes serious eye damage

H400 - Very toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P391 - Collect spillage.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Name : Lauryl Alcohol Ethoxylate (3 Mole)

CAS-No. : 68551-12-2

Name	Product Identifier	%	GHS-US classification
Alcohols, C12-16, ethoxylated	(CAS-No.) 68551-12-2	100	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

3.2. Mixture

Not applicable

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/Injuries: Causes skin irritation. Causes serious eye damage.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Do not get in eyes, on skin, or on clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Industrial Use

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear colorless viscous liquid
Odor	: No data available
Odor Threshold	: No data available
pH	: 6 - 8 (1% solution)
Relative Evaporation Rate (butylacetate=1)	: No data available
Melting Point	: 6 °C (42.8 °F)
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: 160 °C (320 °F) (open glass)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: 11 (calculated)
Relative Density	: No data available
Specific Gravity	: 950 kg/m ³ @ room temperature
Solubility	: Water: Insoluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 32 mPa.s @ 25 °C
Explosive Properties	: No data available
Oxidizing Properties	: No data available
Explosive Limits	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2 Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3 Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5 Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6 Hazardous Decomposition Products:** None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity : Not classified

Skin Corrosion/Irritation: Causes skin irritation.

pH: 6 - 8 (1% solution)

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 6 - 8 (1% solution)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Potential Adverse Human Health Effects and Symptoms: Based on available data, the classification criteria are not met.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Lauryl Alcohol Ethoxylate (3 Mole) (68551-12-2)

12.2. Persistence and Degradability

Lauryl Alcohol Ethoxylate (3 Mole) (68551-12-2)

Persistence and Degradability : May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

Lauryl Alcohol Ethoxylate (3 Mole) (68551-12-2)

Bioaccumulative Potential : Not established.

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued. In Accordance With ICAO/IATA/IMDG/DOT

14.1. UN Number

UN-No.(DOT) : 3082

DOT NA no. UN3082

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.
(Alcohols, C12-16, ethoxylated)

Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Hazard Labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



DOT Symbols : G - Identifies PSN requiring a technical name

Packing Group (DOT) : III - Minor Danger

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
173 - An appropriate generic entry may be used for this material.
335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
14.3. Additional Information
Emergency Response Guide (ERG) Number : 171
Other information : No supplementary information available.

Transport by Sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

EmS-No. (1) : F-A

EmS-No. (2) : S-F

Air Transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : No limit

DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : No limit

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Lauryl Alcohol Ethoxylate (3 Mole) (68551-12-2)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Alcohols, C12-16, ethoxylated (68551-12-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Lauryl Alcohol Ethoxylate (3 Mole)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
---------------------------------	---

15.2 US State Regulations Neither this product nor its chemical components appear on any US state lists.

SECTION 16: OTHER INFORMATION

Date of Preparation or Latest Revision : 05/12/2017
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H315	Causes skin irritation
H318	Causes serious eye damage
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

The data herein are based on our current knowledge and believed to be reliable. Acme-Hardesty Co., provides this information without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

Users must make their own determination that handling, storage, use and disposal of the product in the anticipated manner is safe and appropriate. Because these actions of the user are out of our control, and may be beyond our knowledge, we do not assume responsibility and expressly disclaim liability for loss, damage, expense or any other claim arising out of or in any way connected with the handling, storage, use or disposal of the product or container.

Acme Hardesty US GHS SDS