

Rubber Grade Stearic Acid 60 R Tallow Based

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 12/12/2014 Date of Issue: 07/30/2014

Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product Identifier

Product Form: Mixture

Product Name: Rubber Grade Stearic Acid 60 R Tallow Based

CAS No: 57-11-4

Synonyms: RGSA Tallow Flakes

1.2. Intended Use of the Product

Use of the substance/mixture: Adhesives, resinous and polymeric coatings, components of paper and paperboard in contact with aqueous and fatty foods, rubber articles intended for repeated use, surface lubricants used in the manufacture of metallic articles.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Acme-Hardesty Co.
450 Sentry Parkway
Blue Bell, PA 19422
T 866-226-3834 T 215-591-3610
www.acme-hardesty.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Comb. Dust

2.2. Label Elements

GHS-US Labeling

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : May form combustible dust concentrations in air

2.3. Other Hazards

No additional information available

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Stearic acid	(CAS No) 57-11-4	60 - 100	Comb. Dust

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Rubber Grade Stearic Acid 60 R Tallow Based

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: None expected under normal conditions of use.

Symptoms/Injuries After Inhalation: None expected under normal conditions of use.

Symptoms/Injuries After Skin Contact: Contact during a long period may cause slight irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: If a large quantity has been ingested: May cause nausea, vomiting, and diarrhea.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Alcohol foam, carbon dioxide, dry chemical, sand. For large fire : Water spray.

Unsuitable Extinguishing Media: Do not use water jet.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible Dust

Explosion Hazard: Dust explosion hazard in air; Fine dust clouds may form explosive mixtures with air.

Reactivity: If dust are formed: Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

5.3. Advice for Firefighters

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Technical Measures: Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation. Avoid creating or spreading dust. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep away from heat and direct sunlight.

Incompatible Products: Strong oxidizers.

7.3. Specific End Use(s)

Adhesives, resinous and polymeric coatings, components of paper and paperboard in contact with aqueous and fatty foods, rubber articles intended for repeated use, surface lubricants used in the manufacture of metallic articles.

Rubber Grade Stearic Acid 60 R Tallow Based

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

No Occupational Exposure Limits (OELs) have been established for this product or its chemical components.

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective goggles.



Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical goggles or safety glasses.

Respiratory Protection

: Wear approved mask.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Off-White. Waxy, flakes.
Odor	: Faint
Odor Threshold	: No data available
pH	: Not measurable
Relative Evaporation Rate (butylacetate=1)	: No data available
Melting Point	: 55 °C (131°F)
Freezing Point	: No data available
Boiling Point	: 205 - 225 °C (401 - 437°F) (10 hPa)
Flash Point	: 180 °C (356°F)
Auto-ignition Temperature	: > 350 °C (662°F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.85 g/ml @ 75°C (167 °F)
Solubility	: Insoluble in water.
Partition coefficient	: Estimated > 3
Viscosity	: 10 mPa.s @65°C (149 °F)
Explosive Properties	: No data available
Oxidizing Properties	: No data available
Explosive Limits	: Not applicable

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: If dust are formed ;Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

10.2 Chemical Stability: Stable under normal temperture and pressure.

10.3 Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Rubber Grade Stearic Acid 60 R Tallow Based

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4 Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Sparks, heat, open flame and other sources of ignition.

10.5 Incompatible Materials: Strong oxidizers.

10.6 Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity : Not classified

Skin Corrosion/Irritation: Not classified **pH:** Not measurable

Serious Eye Damage/Irritation: Not classified **pH:** Not measurable

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: None expected under normal conditions of use.

Symptoms/Injuries After Skin Contact: Contact during a long period may cause slight irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: If a large quantity has been ingested: May cause nausea, vomiting, and diarrhea.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity No additional information available

12.2. Persistence and Degradability

Rubber Grade Stearic Acid 60 R Tallow Based (57-11-4)

Persistence and Degradability	Easily biodegradable.
--------------------------------------	-----------------------

12.3. Bioaccumulative Potential

Rubber Grade Stearic Acid 60 R Tallow Based (57-11-4)

Bioaccumulative Potential	Not expected to bioaccumulate.
----------------------------------	--------------------------------

12.4. Mobility in Soil

Stearic acid (57-11-4)

Log Koc	51.05
----------------	-------

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/IMDG/DOT

14.1. UN Number Not regulated for transport

14.2. UN Proper Shipping Name Not regulated for transport

14.3. Additional Information

Other information : No supplementary information available.

Transport by Sea Not regulated for transport

Air Transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Stearic acid (57-11-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2 US State Regulations

Rubber Grade Stearic Acid 60 R Tallow Based

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stearic acid (57-11-4)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: OTHER INFORMATION

Revision date	: 12/12/2014
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Comb. Dust	Combustible Dust
	May form combustible dust concentrations in air

The data herein are based on our current knowledge and believed to be reliable. Acme-Hardesty Co., provides this information without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

Users must make their own determination that handling, storage, use and disposal of the product in the anticipated manner is safe and appropriate. Because these actions of the user are out of our control, and may be beyond our knowledge, we do not assume responsibility and expressly disclaim liability for loss, damage, expense or any other claim arising out of or in any way connected with the handling, storage, use or disposal of the product or container.

SDS US (GHS HazCom) - ACME Hardesty